

RHOMBUS PLUS

HIGH EFFICACY TP(B) BACK-LIT PANEL

Rhombus Plus back-lit panels offer a cost effective combination of high efficacy and TP(b) diffusers. Available in a choice of size formats and 4000K or 6000K.



Features

- High efficacy upto 150 lm/W
- TP(b) diffuser as standard
- 595 x595mm & 595 x 1195mm format
- Emergency options available



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
RBX12640-60	Rhombus Plus 595mm x 1195mm TP(b)	6000 lm		40W	150 lm/W

Product Information

Warranty	5 Years
On-Site Warranty	2 Years
Colour Appearance (CCT)	6000K
IP Rating	IP40
IK Rating	IK03
Voltage	230V
Material (Body/Housing)	Steel & Aluminium
Material (Diffuser/Cover)	TP(b) Rated Styrene
Colour Rendition (CRI)	Ra > 80

Colour Finish	White RAL9003
LED Life Expectancy	L80B50 50,000 Hours
Power Factor	>0.9
Frequency	50/60Hz
Driver Type	Fixed Output
Approval	UKCA CE
Electrical Class	Class II
Working Temperature	-20°C to 45°C

RHOMBUS PLUS

HIGH EFFICACY TP(B) BACK-LIT PANEL

Packaging Information

Dimensions (mm)	L: 1195 x W: 595 x D: 35 mm
Product Net Weight (kg)	3.45 kg
Barcode	5055807623001
Box Dimensions (mm)	L: 1255 x W: 615 x D: 42 mm
Box Gross Weight (kg)	4 kg

Units/Outer Carton	4
Outer Carton Barcode	15055807623008
Outer Carton Dimensions (mm)	L: 1270 x W: 630 x D: 185 mm
Outer Carton Gross Weight (kg)	17.5 kg

