



# Smoke Alarm (9V Battery)

CODE: QFS-BAT-S

Standalone

Elite Series



## Features

- Sealed lithium battery with long battery life
- Photoelectrical sensor to detect smoke and reduce false alarms
- Compliant with EN14604:2005/AC:2008
- Alarm sounder (85dB)



Specification	QFS-BAT-S
Power	DC 9V replaceable battery
Alarm Volume	>85dB (A) at 3m
Alarm Sensitivity	0.10 to 0.16dB/m
Compliance Standard	EN14604:2005/AC:2008
Sound Pattern	ISO8201; [Beep 0.5s > Pause 0.5s > Beep 0.5s > Pause 0.5s > Beep 0.5s > Pause 1.5s; Accompanied by Red LED Flash] [Repeat]
Mounting	Mount onto base
























# Smoke Alarm (9V Battery)

CODE: QFS-BAT-S

Standalone

Elite Series

## Functions

Normal	Red LED flashes once (32 seconds);	  32 
Fault	Buzzer sound every 32 seconds	 32
Low Power	Buzzer sound every 32 seconds	 32
Alarm	Pulsating buzzer; Accompanied by red LED flashing every 1 second	        1
Test	Imitates LED & buzzer pattern as per 'Alarm Mode'	        1

### **WARNING**

Weekly tests should be performed. The batteries are designed to last for 1 year - after this point, the battery must be replaced. In any doubt, an alarm trigger should be assumed to be due to a fire and appropriate measures must be taken immediately.