

POLO COMBI

MULTI-USE IP65 SLIM BULKHEAD

Polo Combi is the perfect solution for virtually any application. Every product features multi-wattage and multi-cct selection. Plus every fitting is supplied with a choice of trims. Add emergency and microwave sensor versions and it is the only bulkhead you need to cover virtually every project.



Features

- Configurable in 36 different ways
- Multi - Wattage / 3 CCT / 3 Trim's
- IP65 and UV stable - outdoor or indoor use
- BESA and conduit entries
- Microwave sensor and emergency options

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
PCB13E-CCT	Polo Combi 230V 13W IP65 Multi-Use Bulkhead with Selectable Wattage and CCT, Multiple Trims and Integral 3 hour Maintained Emergency Conversion	875lm 963lm 1284lm 1395lm	145 lm	8W 9W 12W 13W	107 lm/W

Product Information

Warranty	5 Years
Emergency Battery Warranty	5 Years
Colour Appearance (CCT)	3000K 4000K 6500K
IP Rating	IP65
IK Rating	IK08
Emergency Battery Type	LiFePO4
Voltage	220-240V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate
Colour Rendition (CRI)	Ra >80

Colour Finish	White RAL9003 Black RAL9005
LED Life Expectancy	L70B50 54,000 Hours
Power Factor	0.7/0.8
Frequency	50/60Hz
Driver Type	Fixed Output - Selectable Wattage
Approval	UKCA CE
Electrical Class	Class II
Working Temperature	5°C to 40°C
EM Working Temperature	5°C to 40°C

POLO COMBI

MULTI-USE IP65 SLIM BULKHEAD

Packaging Information

Dimensions (mm)	Ø: 291 x D: 83 mm
Product Net Weight (kg)	0.96 kg
Barcode	5055807624718
Box Dimensions (mm)	L: 296 x W: 296 x D: 128 mm
Box Gross Weight (kg)	1.12 kg

Units/Outer Carton	10
Outer Carton Barcode	15055807624715
Outer Carton Dimensions (mm)	L: 662 x W: 310 x D: 605 mm
Outer Carton Gross Weight (kg)	13.3 kg

