## Knightsbridge




## **CPL6CT**



## 230V 6W CCT Adj Circular LED Panel- 140mm

www.mlaccessories.co.uk



| MLA PART CODE                 | CPL6CT   |
|-------------------------------|--|
| DESCRIPTION                   | 230V 6W CCT Adj Circular LED Panel- 140mm                                    |
| NET WEIGHT (KG)               | 0.18   |
| FINISH                        | White  |
| DIFFUSER                      | Opal   |
| DIMENSIONS (MM)               | Diameter - 140<br>Projection - 15<br>Base Diameter - 94<br>Minimum Void - 50 |
| CUT-OUT (MM)                  | Min./Max. Cut-out - 55 - 100   |
| CONSTRUCTION                  | Construction - Polycarbonate   |
| CLASS                         | II   |
| IP RATING                     | IP20   |
| WATTAGE (W)                   | 6  |
| LAMP TECHNOLOGY               | SMD LED  |
| LAMP INCLUDED                 | Yes  |
| LUMENS (LM)                   | 400/430/410  |
| LUMENS LIGHT SOURCE ONLY (LM) | 655  |
| LUMEN TOLERANCE               | 5%   |
| EFFICACY (LM/W)               | 120.2  |
| CIRCUIT WATTAGE (W)           | 5.49   |
| ССТ                           | 3000/4000/6000K  |
| LIGHT COLOUR                  | CCT  |
| CRI                           | >85  |
| SDCM                          | <6   |
| RUNNING CURRENT (A)           | 0.046  |
| DISPLACEMENT FACTOR           | >0.5   |
| SVM                           | 0.049  |
| PST-LM                        | 0.04   |
| BEAM ANGLE (DEGREES)          | 120  |





## Knightsbridge

| LIFE SPAN (HRS)                          | 30,000        |
|--|---------------|
| L70B50 LIFESPAN (HRS)                    | 30,000        |
| DIMMABLE                                 | No            |
| IC RATED                                 | Yes           |
| OPERATING TEMPERATURE                    | -20~40°C      |
| INPUT VOLTAGE                            | 230V 50Hz     |
| CABLE LENGTH (M)                         | 0.3           |
| WARRANTY                                 | 3year(s)      |
| MANUFACTURED IN ACCORDANCE WITH          | BS EN 60598   |
| ORIGIN OF MANUFACTURE                    | China         |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes           |
| EAN                                      | 5055832983910 |

Date Created: 12/12/2024 08:54





